GI-2

GIS for primary distribution

Our latest developed Gas Insulated Switchgear is the ${\sf SF}_6$ insulated switchgear GI- 2 for single busbar applications and indoor installation.

Our latest Gas Insulated MV SWITCHGEAR GI-2

Innovation and environmental care are the driving forces behind SGC - Switchgear Company. The GI-2 is the result of our more than 40 years of experience in medium voltage switchgear. There are multiple advantages that we can relate to the GI-2. First of all, the GI-2 is a compact solution suitable for heavy industry and power stations. Quality, is our main concern during the development of new products. So our GI-2 is most certainly BUILT TO LAST because of our high quality standards in terms of production. Last but not least, we can say, that the GI-2 is very much a cost effective investment because of the benefits of reduced operating costs and maximum supply reliability.

Some of the features:

- Fixed-mounted circuit breaker GI-2 is factoryassembled and hermetically sealed
- Suitable to use with transformer and switching substations
- Flexible Modular System combination is unlimited
- Suitable for heavy industry
- Can be equipped with a wide range of optional features






SwitchGear Company

THE SPECIALIST IN MEDIUM VOLTAGE SWITCHGEAR

GI-2 | Technical specifications

Rated Voltage	24 kV
Rated power frequency withstand voltage (Ud)	50 kV
Rated lightning impulse withstand voltage (peak)	125 kV
Rated short-circuit breaking current (Isc)	to 25 kA
Rated peak withstand current (Ip)	to 50 kA
Rated short-time withstand current (Ik)	25 kA
Rated duration of short circuit current (tk)	1s
Internal arc withstand current, 1s	20 kA
Rated frequency	50/60 Hz
Rated busbar current	2500 A
Rated feeder current	630 A, 1250 A, 1600 A, 2000 A, 2500 A
Standards	IEC 62271-200 / IEC 62271-1
Degree of protection (RC 630 A, 1250 A)	IP4X
Degree of protection (RC 1600 A, 2000 A)	IP3X
Temperature range	-15°C to +40°C
Maximum relative humidity	95%
Maximum altitude	1000m *



*For installations at altitudes higher than 1000 m, the insulation withstand level of external insulation at the service location has to be determined by multiplying the rated insulation levels by a factor Ka in accordance to IEC standards.

SGC stands for:

- Optimal operator safety.
- User friendly, IEC certified, built to last products.
- Modern technology & ergonomic, eco-friendly production processes.
- Made-to-measure & optionally customer labeled.





SGC - Switchgear Company nv Moorstraat 24 - 9850 Landegem Belgium

(+32 (0)9 321 91 12

www.switchgearcompany.eu

info@switchgearcompany.eu

Follow us: 🚹 in 🖸

SGC - SwitchGear Company nv.

Medium voltage switchgear, built to last.

SGC - SwitchGear Company nv has been supplying reliable products for electrical distribution for more than 40 years. Innovative ideas and environmental care are the driving forces behind SGC - SwitchGear Company nv. The development of complete solutions consists of a minimum number of components, all of which have an exceptional life span. SGC - SwitchGear Company nv stands for exceptional quality and superior customer care. Your desired specifications and deadlines are our main concern. An exclusive factory and highly automated production lines are key factors in our "state of the art" components and systems. It enables us to develop the DF-2, DR-6/DT-6, DF-3 ,DI-2, SI-2, DW-2, N₂ Blue, DF₂ Blue and GI-2 to the highest quality standards. When it comes to delivery times, prices and products SGC - SwitchGear Company nv delivers.